



VALO TRACK


OPAL DIFFUSER

220-240V AC 50/60Hz Design: INHOUSE

Zylindrische Stromschienenleuchte · sehr homogene Ausleuchtung · 230V Spannungsversorgung, ohne rückseitige 48V Stromschiene
 Pendant in cylindric shape · homogeneous lighting · 230V power supply, without rear 48V power rail
 Lampada a sospensione con struttura cilindrica · alimentazione 230V, senza barra di alimentazione 48V posteriore
 Lampe à suspension avec couvercle cylindrique · alimentation 230V, sans rail d'alimentation arrière 48V

SYS 24W	L: 1146mm	LM
720-0083210WWXXY		2340 - 2580

355°



IP20  

COMPLETE CODE																
WW = LIGHT COLOUR	XX = COLOUR	Y = DIMMBAR / DIMMABLE														
<table border="1"> <tr> <td>W2</td> <td>LED 2700K = 23 CRI>90</td> </tr> <tr> <td>W3</td> <td>LED 3000K = 29 CRI>90</td> </tr> <tr> <td>W4</td> <td>LED 4000K = 24 CRI>90</td> </tr> </table>	W2	LED 2700K = 23 CRI>90	W3	LED 3000K = 29 CRI>90	W4	LED 4000K = 24 CRI>90	<table border="1"> <tr> <td>W</td> <td>white = 55</td> </tr> </table>	W	white = 55	<table border="1"> <tr> <td>S</td> <td>switchable = 0</td> </tr> <tr> <td>D</td> <td>DALI dimm. = d</td> </tr> <tr> <td>B</td> <td>BLUETOOTH dimm. = b</td> </tr> </table>	S	switchable = 0	D	DALI dimm. = d	B	BLUETOOTH dimm. = b
W2	LED 2700K = 23 CRI>90															
W3	LED 3000K = 29 CRI>90															
W4	LED 4000K = 24 CRI>90															
W	white = 55															
S	switchable = 0															
D	DALI dimm. = d															
B	BLUETOOTH dimm. = b															