

Beräkning av bländning enligt UGR

| p Tak | 70 | 70 | 50 | 50 | 30 | 70 | 70 | 50 | 50 | 30 | |
|--------------------|-----|------------------------------------|------|------|------|------|------------------------------------|------|------|------|------|
| p Vägg | 50 | 30 | 50 | 30 | 30 | 50 | 30 | 50 | 30 | 30 | |
| p Golv | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | |
| Rumsstorlek X Y | | Blickriktning tvärs till tvärsaxel | | | | | Blickriktning längs till tvärsaxel | | | | |
| 2H | 2H | 22.6 | 23.7 | 22.9 | 23.9 | 24.2 | 24.9 | 26.0 | 25.3 | 26.3 | 26.5 |
| 2H | 3H | 24.1 | 25.1 | 24.4 | 25.3 | 25.6 | 25.3 | 26.3 | 25.6 | 26.6 | 26.9 |
| 2H | 4H | 24.7 | 25.6 | 25.0 | 25.9 | 26.2 | 25.6 | 26.5 | 25.9 | 26.8 | 27.1 |
| 2H | 6H | 25.1 | 26.0 | 25.5 | 26.3 | 26.7 | 25.8 | 26.7 | 26.2 | 27.0 | 27.3 |
| 2H | 8H | 25.3 | 26.1 | 25.7 | 26.5 | 26.8 | 25.9 | 26.7 | 26.3 | 27.1 | 27.4 |
| 2H | 12H | 25.4 | 26.2 | 25.8 | 26.5 | 26.9 | 26.0 | 26.8 | 26.4 | 27.1 | 27.5 |
| 4H | 2H | 23.3 | 24.2 | 23.6 | 24.5 | 24.8 | 25.2 | 26.1 | 25.5 | 26.4 | 26.7 |
| 4H | 3H | 25.0 | 25.8 | 25.4 | 26.1 | 26.5 | 25.8 | 26.6 | 26.2 | 27.0 | 27.3 |
| 4H | 4H | 25.7 | 26.4 | 26.1 | 26.8 | 27.2 | 26.2 | 26.9 | 26.6 | 27.3 | 27.7 |
| 4H | 6H | 26.3 | 26.9 | 26.7 | 27.3 | 27.7 | 26.6 | 27.2 | 27.0 | 27.6 | 28.0 |
| 4H | 8H | 26.5 | 27.1 | 27.0 | 27.5 | 27.9 | 26.8 | 27.3 | 27.2 | 27.7 | 28.2 |
| 4H | 12H | 26.7 | 27.1 | 27.1 | 27.6 | 28.1 | 26.9 | 27.4 | 27.3 | 27.8 | 28.3 |
| 8H | 4H | 26.0 | 26.5 | 26.4 | 27.0 | 27.4 | 26.5 | 27.0 | 26.9 | 27.4 | 27.9 |
| 8H | 6H | 26.7 | 27.2 | 27.2 | 27.6 | 28.1 | 27.0 | 27.4 | 27.5 | 27.9 | 28.4 |
| 8H | 8H | 27.0 | 27.4 | 27.5 | 27.9 | 28.4 | 27.2 | 27.6 | 27.7 | 28.1 | 28.6 |
| 8H | 12H | 27.2 | 27.6 | 27.8 | 28.1 | 28.6 | 27.4 | 27.7 | 27.9 | 28.2 | 28.8 |
| 12H | 4H | 26.0 | 26.5 | 26.5 | 26.9 | 27.4 | 26.5 | 27.0 | 26.9 | 27.4 | 27.9 |
| 12H | 6H | 26.8 | 27.2 | 27.3 | 27.7 | 28.2 | 27.0 | 27.4 | 27.5 | 27.9 | 28.4 |
| 12H | 8H | 27.1 | 27.5 | 27.6 | 28.0 | 28.5 | 27.3 | 27.6 | 27.8 | 28.1 | 28.7 |

Variation av åskådarposition för tvärsaxeländ S

| | | |
|-------------------|-------------|-------------|
| S = 1.0H | +0.2 / -0.1 | +0.6 / -0.5 |
| S = 1.5H | +0.3 / -0.4 | +1.8 / -1.6 |
| S = 2.0H | +0.4 / -0.7 | +3.1 / -2.1 |
| Standardtabell | BK06 | BK03 |
| Korrektionsfaktor | 9.8 | 9.3 |

Korrigerade bländindikeringar relaterade till totalt ljusflöde