

## Beräkning av bländning enligt UGR

p Tak	70	70	50	50	30	70	70	50	50	30
p Vägg	50	30	50	30	30	50	30	50	30	30
p Golv	20	20	20	20	20	20	20	20	20	20

Rumsstorlek		Blickriktning tvärs till tvärsaxel					Blickriktning längs till tvärsaxel				
X	Y										
2H	2H	16.8	17.5	17.6	18.4	19.5	22.1	22.9	23.0	23.7	24.8
2H	3H	17.1	17.7	18.0	18.6	19.8	22.4	23.1	23.3	24.0	25.1
2H	4H	17.3	17.9	18.3	18.8	20.0	22.3	22.9	23.2	23.8	25.0
2H	6H	17.6	18.2	18.5	19.1	20.3	22.2	22.7	23.1	23.7	24.9
2H	8H	17.7	18.2	18.7	19.2	20.4	22.1	22.7	23.1	23.6	24.8
2H	12H	17.8	18.3	18.8	19.3	20.5	22.1	22.6	23.1	23.5	24.7
4H	2H	17.1	17.7	18.0	18.6	19.8	21.9	22.5	22.8	23.4	24.5
4H	3H	17.6	18.1	18.5	19.0	20.2	22.2	22.7	23.1	23.6	24.8
4H	4H	17.9	18.3	18.9	19.3	20.5	22.1	22.5	23.1	23.5	24.7
4H	6H	18.3	18.7	19.3	19.7	20.9	22.0	22.4	23.0	23.4	24.6
4H	8H	18.5	18.9	19.5	19.8	21.1	22.0	22.3	23.0	23.3	24.6
4H	12H	18.7	19.0	19.7	20.0	21.3	22.0	22.3	23.0	23.3	24.5
8H	4H	17.9	18.3	18.9	19.3	20.5	21.9	22.3	22.9	23.3	24.5
8H	6H	18.5	18.8	19.6	19.8	21.1	21.9	22.2	22.9	23.2	24.5
8H	8H	18.9	19.1	19.9	20.1	21.4	21.9	22.2	22.9	23.2	24.5
8H	12H	19.2	19.4	20.2	20.4	21.7	21.9	22.1	23.0	23.2	24.5
12H	4H	17.9	18.2	18.9	19.2	20.5	21.9	22.2	22.9	23.2	24.5
12H	6H	18.6	18.8	19.6	19.8	21.1	21.9	22.1	22.9	23.1	24.4
12H	8H	18.9	19.1	20.0	20.2	21.5	21.9	22.1	22.9	23.1	24.5

Variation av åskådarposition för tvärsaxel S

S = 1.0H	+0.7 / -1.1	+0.6 / -0.7
S = 1.5H	+1.4 / -1.6	+0.7 / -0.7
S = 2.0H	+2.2 / -1.9	+2.2 / -3.9
Standardtabell	BK04	BK01
Korrektionsfaktor	2.7	5.6

Korrigerade bländindikeringar relaterade till totalt ljusflöde