

Beräkning av blandning enligt UGR

ρ Tak		60	70	70	50	50	60	70	70	50	50
ρ Vågg		60	50	30	50	30	60	50	30	50	30
ρ Golv		30	30	30	30	30	30	30	30	30	30
Rumsstorlek X	Y	Blickriktning tvärs till tvärsaxel					Blickriktning längs till tvärsaxel				
2H	2H	18.1	19.7	21.0	20.1	21.4	18.1	19.7	21.1	20.1	21.4
2H	3H	20.1	21.9	23.2	22.4	23.8	20.3	22.0	23.2	22.4	23.6
2H	4H	21.5	23.1	24.3	23.6	24.7	21.5	23.2	24.3	23.6	24.8
2H	6H	22.7	24.4	25.5	24.9	25.9	22.8	24.4	25.5	24.9	26.0
2H	8H	23.4	25.1	26.1	25.6	26.6	23.5	25.1	26.2	25.6	26.7
2H	12H	24.2	25.9	26.9	26.4	27.3	24.2	25.9	26.9	26.4	27.4
4H	2H	18.9	20.5	21.7	21.0	22.1	18.9	20.6	21.7	21.0	22.2
4H	3H	21.2	22.0	24.0	23.5	24.5	21.4	23.0	24.0	23.5	24.5
4H	4H	22.7	24.4	25.3	24.9	25.8	22.7	24.4	25.3	24.9	25.8
4H	6H	24.1	25.8	26.6	26.4	27.2	24.2	25.9	26.7	26.4	27.2
4H	8H	24.9	26.6	27.4	27.2	27.9	24.9	26.7	27.4	27.2	28.0
4H	12H	25.6	27.5	28.2	28.1	28.8	25.8	27.6	28.3	28.1	28.8
6H	4H	23.2	24.9	25.7	25.5	26.2	23.2	25.0	25.7	25.5	26.3
6H	6H	24.9	26.7	27.3	27.3	27.9	25.0	26.7	27.3	27.3	27.9
6H	8H	25.9	27.6	28.2	28.2	28.8	25.9	27.7	28.2	28.2	28.8
6H	12H	27.0	28.7	29.2	29.4	29.8	27.0	28.8	29.3	29.4	29.9
12H	4H	23.3	25.1	25.8	25.7	26.3	23.4	25.1	25.8	25.7	26.3
12H	6H	25.1	26.9	27.5	27.5	28.1	25.2	26.9	27.5	27.5	28.1
12H	8H	26.2	28.0	28.5	28.6	29.1	26.2	28.0	28.5	28.6	29.1

Variation av blickriktning för tvärsaxel S

S = 1.0H	+0.1 / -0.1
S = 1.5H	+0.3 / -0.3
S = 2.0H	+0.4 / -0.4
Standardtabel	IK11
Korrektionsfaktor	12.1

Kontrollerade blickriktning för tvärsaxel till totalt ljusflöde