

Beräkning av blandning enligt UGR

ρ Tak	60	70	70	50	50	60	70	70	50	50	
ρ Vågg	60	50	30	50	30	60	50	30	50	30	
ρ Golv	30	30	30	30	30	30	30	30	30	30	
Rumsstorlek X	Y	Blickriktning tvärs till tvärsaxel					Blickriktning längs till tvärsaxel				
2H	2H	29.3	30.9	32.2	31.3	32.7	29.4	31.0	32.3	31.4	32.8
2H	3H	31.6	33.3	34.5	33.7	35.0	31.9	33.5	34.7	34.0	35.2
2H	4H	33.9	34.5	35.7	35.0	36.2	33.3	34.9	36.1	35.4	36.5
2H	6H	34.2	35.9	37.0	36.4	37.5	34.8	36.4	37.5	36.9	38.0
2H	8H	35.0	36.6	37.7	37.2	38.2	35.6	37.2	38.3	37.8	38.8
2H	12H	35.8	37.5	38.5	38.0	39.0	36.5	38.2	39.2	38.7	39.7
4H	2H	30.2	31.8	33.0	32.3	33.4	30.2	31.9	33.0	32.4	33.5
4H	3H	32.7	34.4	35.4	34.9	35.9	32.9	34.6	35.6	35.1	36.1
4H	4H	34.1	35.8	36.7	36.4	37.3	34.5	36.1	37.1	36.7	37.6
4H	6H	35.7	37.3	38.2	37.9	38.7	36.2	37.9	38.7	38.4	39.2
4H	8H	36.5	38.2	38.9	38.8	39.5	37.1	38.8	39.6	39.4	40.1
4H	12H	37.4	39.1	39.8	39.8	40.4	38.1	39.8	40.5	40.4	41.1
8H	4H	34.7	36.4	37.2	37.0	37.8	35.0	36.7	37.5	37.3	38.0
8H	6H	36.5	38.2	38.9	38.9	39.5	37.0	38.7	39.3	39.3	39.9
8H	8H	37.5	39.3	39.8	39.9	40.5	38.1	39.8	40.4	40.4	41.0
8H	12H	38.7	40.4	40.9	41.1	41.6	39.4	41.1	41.6	41.7	42.2
12H	4H	34.9	36.6	37.3	37.3	37.9	35.1	36.8	37.5	37.4	38.1
12H	6H	36.8	38.5	39.1	39.1	39.7	37.2	38.9	39.5	39.5	40.1
12H	8H	37.9	39.6	40.1	40.3	40.8	38.4	40.1	40.6	40.8	41.3

Variation av blickriktningar för tvärsaxeländ S

S = 1.0H	+0.1 / -0.1	+0.1 / -0.1
S = 1.5H	+0.3 / -0.3	+0.3 / -0.3
S = 2.0H	+0.4 / -0.4	+0.4 / -0.5
Standardtabell	0K12	0K12
Korrektionsfaktor	24.1	24.6

Kontrollerade blickriktningarna relativt till totalt ljusflöde