

Beräkning av blandning enligt UGR

p Tak	60	70	70	50	50	60	70	70	50	50	
p Vägg	60	50	30	50	30	60	50	30	50	30	
p Golv	30	20	20	20	20	30	20	20	20	20	
Rumsstorlek X	Y	Blickriktning tvärs till tvärsaxel						Blickriktning längs till tvärsaxel			
2H	2H	15.8	17.3	18.3	18.0	18.9	15.8	17.4	18.3	18.1	19.0
2H	3H	16.9	18.4	19.3	19.1	20.0	17.0	18.5	19.4	19.3	20.1
2H	4H	17.2	18.8	19.6	19.5	20.3	17.4	18.9	19.7	19.7	20.5
2H	6H	17.4	18.9	19.7	19.7	20.4	17.6	19.1	19.9	19.9	20.6
2H	8H	17.4	18.9	19.6	19.7	20.4	17.6	19.2	19.9	19.9	20.6
2H	12H	17.4	18.9	19.6	19.7	20.3	17.6	19.1	19.8	19.9	20.6
4H	2H	16.2	17.8	18.6	18.5	19.3	16.3	17.8	18.6	18.6	19.3
4H	3H	17.5	19.0	19.7	19.8	20.5	17.6	19.1	19.8	19.9	20.6
4H	4H	17.9	19.5	20.1	20.3	20.9	18.1	19.6	20.2	20.4	21.0
4H	6H	18.2	19.7	20.2	20.5	21.0	18.4	19.9	20.4	20.7	21.2
4H	8H	18.2	19.8	20.2	20.6	21.0	18.4	20.0	20.4	20.8	21.2
4H	12H	18.2	19.7	20.2	20.6	21.0	18.4	20.0	20.4	20.8	21.2
8H	4H	18.0	19.6	20.1	20.4	20.9	18.2	19.7	20.2	20.5	21.0
8H	6H	18.4	19.9	20.3	20.8	21.1	18.5	20.1	20.5	20.9	21.3
8H	8H	18.4	20.0	20.3	20.9	21.2	18.6	20.2	20.5	21.1	21.4
8H	12H	18.4	20.0	20.3	20.9	21.1	18.6	20.2	20.5	21.1	21.3
12H	4H	18.0	19.6	20.0	20.4	20.8	18.1	19.7	20.1	20.5	20.9
12H	6H	18.3	19.9	20.2	20.8	21.1	18.5	20.1	20.4	20.9	21.3
12H	8H	18.4	20.0	20.3	20.9	21.1	18.6	20.2	20.5	21.1	21.3

Variation av åskådarposition för bäravstånd S

S = 1.0H	+0.2 / -0.2	+0.1 / -0.2
S = 1.5H	+0.3 / -0.6	+0.3 / -0.5
S = 2.0H	+0.6 / -1.1	+0.6 / -0.9

Standardtabell	BK04	BK04
Korrektionsfaktor	3.5	3.6

Konjugerade blandindikeringar relaterade till total ljusflöde