

Beräkning av blandning enligt UGR

| | | | | | | | | | | |
|--------|----|----|----|----|----|----|----|----|----|----|
| p Tak | 60 | 70 | 70 | 50 | 50 | 60 | 70 | 70 | 50 | 50 |
| p Vägg | 60 | 50 | 30 | 50 | 30 | 60 | 50 | 30 | 50 | 30 |
| p Golv | 30 | 20 | 20 | 20 | 20 | 30 | 20 | 20 | 20 | 20 |

| Rumsstorlek X | Y | Blickriktning tvärs till tvärsaxel | | | | | Blickriktning längs till tvärsaxel | | | | |
|------------------|-----|------------------------------------|------|------|------|------|------------------------------------|------|------|------|------|
| 2H | 2H | 17.4 | 19.2 | 19.9 | 19.4 | 20.1 | 17.3 | 19.0 | 19.8 | 19.3 | 20.0 |
| 2H | 3H | 17.2 | 19.0 | 19.7 | 19.3 | 20.0 | 17.1 | 18.9 | 19.6 | 19.2 | 19.8 |
| 2H | 4H | 17.1 | 19.0 | 19.6 | 19.3 | 19.9 | 17.0 | 18.8 | 19.5 | 19.2 | 19.8 |
| 2H | 6H | 17.0 | 18.9 | 19.5 | 19.2 | 19.8 | 16.9 | 18.8 | 19.3 | 19.1 | 19.7 |
| 2H | 8H | 17.0 | 18.8 | 19.4 | 19.2 | 19.7 | 16.9 | 18.7 | 19.3 | 19.1 | 19.6 |
| 2H | 12H | 16.9 | 18.8 | 19.3 | 19.2 | 19.7 | 16.8 | 18.7 | 19.2 | 19.1 | 19.6 |
| 4H | 2H | 17.1 | 19.0 | 19.6 | 19.3 | 19.9 | 17.0 | 18.8 | 19.5 | 19.2 | 19.8 |
| 4H | 3H | 17.0 | 18.8 | 19.3 | 19.2 | 19.7 | 16.8 | 18.7 | 19.2 | 19.1 | 19.6 |
| 4H | 4H | 16.9 | 18.7 | 19.2 | 19.1 | 19.6 | 16.7 | 18.6 | 19.1 | 19.0 | 19.4 |
| 4H | 6H | 16.8 | 18.7 | 19.1 | 19.1 | 19.4 | 16.6 | 18.6 | 18.9 | 19.0 | 19.3 |
| 4H | 8H | 16.7 | 18.6 | 19.0 | 19.1 | 19.4 | 16.6 | 18.5 | 18.9 | 19.0 | 19.3 |
| 4H | 12H | 16.7 | 18.6 | 18.9 | 19.1 | 19.3 | 16.6 | 18.5 | 18.8 | 18.9 | 19.2 |
| 8H | 4H | 16.7 | 18.6 | 19.0 | 19.1 | 19.4 | 16.6 | 18.5 | 18.8 | 19.0 | 19.3 |
| 8H | 6H | 16.6 | 18.5 | 18.8 | 19.0 | 19.3 | 16.5 | 18.4 | 18.7 | 18.9 | 19.1 |
| 8H | 8H | 16.6 | 18.5 | 18.7 | 19.0 | 19.2 | 16.4 | 18.4 | 18.6 | 18.9 | 19.1 |
| 8H | 12H | 16.5 | 18.5 | 18.7 | 19.0 | 19.1 | 16.4 | 18.3 | 18.5 | 18.9 | 19.0 |
| 12H | 4H | 16.7 | 18.6 | 18.9 | 19.0 | 19.3 | 16.5 | 18.5 | 18.8 | 18.9 | 19.2 |
| 12H | 6H | 16.5 | 18.5 | 18.7 | 19.0 | 19.2 | 16.4 | 18.4 | 18.6 | 18.9 | 19.1 |
| 12H | 8H | 16.5 | 18.5 | 18.6 | 19.0 | 19.1 | 16.4 | 18.3 | 18.5 | 18.8 | 19.0 |

Variation av åskådarposition för bäravstånd S

| | | |
|----------|--------------|--------------|
| S = 1.0H | +3.3 / -9.3 | +3.4 / -9.6 |
| S = 1.5H | +5.9 / -13.1 | +6.0 / -13.6 |
| S = 2.0H | +7.9 / -15.5 | +8.0 / -15.8 |

| | | |
|-------------------|------|------|
| Standardtabell | BK00 | BK00 |
| Korrektionsfaktor | 0.6 | 0.4 |

Konjugerade blandindikeringar relaterade till total ljusflöde