

Beräkning av blandning enligt UGR

| p Tak | 60 | 70 | 70 | 50 | 50 | 60 | 70 | 70 | 50 | 50 | |
|------------------|-----|------------------------------------|------|------|------|------|------------------------------------|------|------|------|------|
| p Vågg | 60 | 50 | 30 | 50 | 30 | 60 | 50 | 30 | 50 | 30 | |
| p Golv | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | |
| Rumsstorlek X | Y | Blickriktning tvärs till tvärssekt | | | | | Blickriktning längs till tvärssekt | | | | |
| 2H | 2H | 22.3 | 23.8 | 24.8 | 24.6 | 25.6 | 22.3 | 23.8 | 24.8 | 24.6 | 25.6 |
| 2H | 3H | 25.5 | 26.9 | 27.9 | 27.8 | 28.7 | 25.5 | 26.9 | 27.9 | 27.8 | 28.7 |
| 2H | 4H | 27.7 | 28.7 | 29.6 | 29.6 | 30.5 | 27.7 | 28.7 | 29.6 | 29.6 | 30.5 |
| 2H | 6H | 29.3 | 30.7 | 31.6 | 31.6 | 32.5 | 29.3 | 30.7 | 31.6 | 31.6 | 32.5 |
| 2H | 8H | 30.4 | 31.9 | 32.6 | 32.8 | 33.6 | 30.4 | 31.9 | 32.6 | 32.8 | 33.6 |
| 2H | 12H | 31.7 | 33.1 | 33.9 | 34.0 | 34.8 | 31.7 | 33.1 | 33.9 | 34.0 | 34.8 |
| 4H | 2H | 23.4 | 24.8 | 25.7 | 25.7 | 26.6 | 23.4 | 24.8 | 25.7 | 25.7 | 26.6 |
| 4H | 3H | 26.7 | 28.1 | 28.9 | 29.0 | 29.8 | 26.7 | 28.1 | 28.9 | 29.0 | 29.8 |
| 4H | 4H | 28.6 | 30.1 | 30.8 | 31.0 | 31.7 | 28.6 | 30.1 | 30.8 | 31.0 | 31.7 |
| 4H | 6H | 30.8 | 32.2 | 32.8 | 33.2 | 33.8 | 30.8 | 32.2 | 32.8 | 33.2 | 33.8 |
| 4H | 8H | 32.0 | 33.5 | 34.0 | 34.4 | 35.0 | 32.0 | 33.5 | 34.0 | 34.4 | 35.0 |
| 4H | 12H | 33.4 | 34.8 | 35.4 | 35.8 | 36.3 | 33.4 | 34.8 | 35.4 | 35.8 | 36.3 |
| 8H | 4H | 29.4 | 30.8 | 31.4 | 31.8 | 32.3 | 29.4 | 30.8 | 31.4 | 31.8 | 32.3 |
| 8H | 6H | 31.8 | 33.3 | 33.7 | 34.2 | 34.7 | 31.8 | 33.3 | 33.7 | 34.2 | 34.7 |
| 8H | 8H | 33.2 | 34.7 | 35.1 | 35.6 | 36.1 | 33.2 | 34.7 | 35.1 | 35.6 | 36.1 |
| 8H | 12H | 34.8 | 36.3 | 36.6 | 37.2 | 37.6 | 34.8 | 36.3 | 36.6 | 37.2 | 37.6 |
| 12H | 4H | 29.6 | 31.0 | 31.6 | 32.0 | 32.5 | 29.6 | 31.0 | 31.6 | 32.0 | 32.5 |
| 12H | 6H | 32.1 | 33.6 | 34.0 | 34.6 | 35.0 | 32.1 | 33.6 | 34.0 | 34.6 | 35.0 |
| 12H | 8H | 33.6 | 35.1 | 35.5 | 36.1 | 36.5 | 33.6 | 35.1 | 35.5 | 36.1 | 36.5 |

Variation av blickriktning för tvärssekt S

| | |
|-------------------|-------------|
| S = 1.0H | +0.2 / -0.2 |
| S = 1.5H | +0.3 / -0.3 |
| S = 2.0H | +0.5 / -0.5 |
| Standardtabell | ---- |
| Korrektionsfaktor | ---- |

Kontrollerade blickriktning för relativt till totalt ljusflöde