

Beräkning av blandning enligt UGR

p Tak	60	70	70	50	50	60	70	70	50	50	
p Vågg	60	50	30	50	30	60	50	30	50	30	
p Golv	30	30	30	30	30	30	30	30	30	30	
Rumsstorlek X	Y	Blickriktning tvärs till tvärssekt					Blickriktning längs till tvärssekt				
2H	2H	21.4	23.1	24.3	23.4	24.5	19.8	21.5	22.7	21.8	22.9
2H	3H	22.6	24.4	25.5	24.7	25.7	20.2	22.0	23.1	22.3	23.3
2H	4H	23.1	24.9	25.9	25.2	26.1	20.4	22.1	23.2	22.5	23.4
2H	6H	23.4	25.2	26.1	25.5	26.4	20.4	22.2	23.2	22.6	23.5
2H	8H	23.4	25.2	26.1	25.6	26.4	20.4	22.2	23.1	22.6	23.4
2H	12H	23.4	25.2	26.0	25.6	26.4	20.4	22.2	23.1	22.6	23.4
4H	2H	21.7	23.5	24.5	23.8	24.8	20.4	22.2	23.2	22.5	23.4
4H	3H	22.2	25.0	25.8	25.3	26.2	21.0	22.8	23.7	23.2	24.0
4H	4H	23.7	25.6	26.3	26.0	26.7	21.2	23.0	23.8	23.4	24.1
4H	6H	24.1	26.0	26.6	26.4	27.0	21.3	23.2	23.8	23.6	24.2
4H	8H	24.2	26.1	26.7	26.5	27.1	21.3	23.2	23.8	23.6	24.2
4H	12H	24.2	26.1	26.6	26.5	27.0	21.3	23.2	23.7	23.6	24.1
6H	4H	23.8	25.7	26.3	26.1	26.6	21.4	23.3	23.9	23.7	24.3
6H	6H	24.3	26.2	26.6	26.6	27.1	21.6	23.5	24.0	24.0	24.4
6H	8H	24.3	26.3	26.7	26.7	27.1	21.6	23.6	24.0	24.0	24.4
6H	12H	24.3	26.3	26.6	26.7	27.1	21.6	23.5	23.9	24.0	24.4
12H	4H	23.7	25.6	26.3	26.1	26.6	21.4	23.3	23.9	23.8	24.3
12H	6H	24.2	26.2	26.6	26.6	27.0	21.6	23.6	24.0	24.0	24.4
12H	8H	24.3	26.3	26.6	26.8	27.1	21.7	23.6	24.0	24.1	24.4

Variation av blickriktning för tvärssekt S

S = 1.0H	+0.1 / -0.2	+0.3 / -0.5
S = 1.5H	+0.3 / -0.5	+0.7 / -1.4
S = 2.0H	+0.6 / -0.9	+1.3 / -2.4
Standardtabell	BK04	BK03
Korrektionsfaktor	0.5	0.8

Kontrollerade blickriktning för relativt till totalt ljusflöde