

Beräkning av bländning enligt UGR

| p Tak | | 60 | 70 | 70 | 50 | 50 | 80 | 70 | 70 | 50 | 50 |
|--------------------|-----|------------------------------------|------|------|------|------|------------------------------------|------|------|------|------|
| p Vägg | | 60 | 50 | 30 | 50 | 30 | 60 | 50 | 30 | 50 | 30 |
| p Golv | | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 |
| Rumsstorlek X Y | | Blickriktning tvärs till tvärsaxel | | | | | Blickriktning längs till tvärsaxel | | | | |
| 2H | 2H | 21.4 | 23.1 | 24.3 | 23.4 | 24.5 | 19.8 | 21.5 | 22.7 | 21.8 | 22.9 |
| 2H | 3H | 22.6 | 24.4 | 25.5 | 24.7 | 25.7 | 20.2 | 22.0 | 23.1 | 22.3 | 23.3 |
| 2H | 4H | 23.1 | 24.9 | 25.9 | 25.2 | 26.1 | 20.4 | 22.1 | 23.2 | 22.5 | 23.4 |
| 2H | 6H | 23.4 | 25.2 | 26.1 | 25.5 | 26.4 | 20.4 | 22.2 | 23.2 | 22.6 | 23.5 |
| 2H | 8H | 23.4 | 25.2 | 26.1 | 25.6 | 26.4 | 20.4 | 22.2 | 23.1 | 22.6 | 23.4 |
| 2H | 12H | 23.4 | 25.2 | 26.0 | 25.6 | 26.4 | 20.4 | 22.2 | 23.1 | 22.6 | 23.4 |
| 4H | 2H | 21.7 | 23.8 | 24.8 | 23.8 | 24.8 | 20.4 | 22.2 | 23.2 | 22.8 | 23.4 |
| 4H | 3H | 23.2 | 25.0 | 25.8 | 25.3 | 26.2 | 21.0 | 22.8 | 23.7 | 23.2 | 24.0 |
| 4H | 4H | 23.7 | 25.6 | 26.3 | 26.0 | 26.7 | 21.2 | 23.0 | 23.8 | 23.4 | 24.1 |
| 4H | 6H | 24.1 | 26.0 | 26.6 | 26.4 | 27.0 | 21.3 | 23.2 | 23.8 | 23.6 | 24.2 |
| 4H | 8H | 24.2 | 26.1 | 26.7 | 26.5 | 27.1 | 21.3 | 23.2 | 23.8 | 23.6 | 24.2 |
| 4H | 12H | 24.2 | 26.1 | 26.6 | 26.5 | 27.0 | 21.3 | 23.2 | 23.7 | 23.6 | 24.1 |
| 8H | 4H | 23.8 | 25.7 | 26.3 | 26.1 | 26.6 | 21.4 | 23.3 | 23.9 | 23.7 | 24.3 |
| 8H | 6H | 24.3 | 26.2 | 26.6 | 26.6 | 27.1 | 21.6 | 23.5 | 24.0 | 24.0 | 24.4 |
| 8H | 8H | 24.3 | 26.3 | 26.7 | 26.7 | 27.1 | 21.6 | 23.6 | 24.0 | 24.0 | 24.4 |
| 8H | 12H | 24.3 | 26.3 | 26.6 | 26.7 | 27.1 | 21.6 | 23.5 | 23.9 | 24.0 | 24.4 |
| 12H | 4H | 23.7 | 25.6 | 26.2 | 26.1 | 26.6 | 21.4 | 23.3 | 23.9 | 23.8 | 24.3 |
| 12H | 6H | 24.2 | 26.2 | 26.6 | 26.6 | 27.0 | 21.6 | 23.6 | 24.0 | 24.0 | 24.4 |
| 12H | 8H | 24.3 | 26.3 | 26.6 | 26.8 | 27.1 | 21.7 | 23.6 | 24.0 | 24.1 | 24.4 |

Variation av blicksposition för tvärsaxelnd S

| | | |
|----------------------------------|---|---|
| S = 1.0H S = 1.5H S = 2.0H | +0.1 / -0.2 +0.3 / -0.5 +0.6 / -0.9 | +0.3 / -0.5 +0.7 / -1.4 +1.3 / -2.4 |
| Standardtabell | B004 | B003 |
| Korrektionsfaktor | 8.5 | 5.8 |

Korrigerade bländningsvärden relaterade till total ljusflöde