

Beräkning av bländning enligt UGR

p Tak	60	70	70	80	80	80	70	70	80	80	
p Vägg	60	50	30	50	30	60	50	30	50	30	
p Golv	30	20	20	20	20	30	20	20	20	20	
Rumsstorlek		Blickriktning tvärs till tvärsaxel					Blickriktning längs till tvärsaxel				
X	Y										
2H	2H	10.5	12.3	13.1	12.6	13.3	11.9	13.7	14.5	14.0	14.7
2H	3H	10.5	12.3	13.0	12.6	13.2	11.8	13.7	14.3	13.9	14.6
2H	4H	10.4	12.3	12.9	12.6	13.2	11.8	13.6	14.3	13.9	14.5
2H	6H	10.4	12.3	12.9	12.6	13.2	11.7	13.6	14.2	13.9	14.5
2H	8H	10.4	12.3	12.8	12.6	13.1	11.7	13.5	14.1	13.9	14.4
2H	12H	10.4	12.3	12.8	12.6	13.1	11.6	13.5	14.1	13.9	14.4
4H	2H	10.3	12.2	12.8	12.5	13.1	11.7	13.6	14.2	13.9	14.5
4H	3H	10.3	12.2	12.8	12.6	13.1	11.6	13.5	14.1	13.9	14.4
4H	4H	10.4	12.3	12.7	12.6	13.1	11.6	13.5	14.0	13.9	14.3
4H	6H	10.4	12.3	12.7	12.7	13.0	11.6	13.5	13.9	13.9	14.2
4H	8H	10.3	12.3	12.6	12.7	13.0	11.5	13.5	13.8	13.9	14.2
4H	12H	10.3	12.3	12.6	12.7	13.0	11.5	13.4	13.8	13.9	14.2
8H	4H	10.3	12.2	12.6	12.6	12.9	11.5	13.4	13.8	13.9	14.2
8H	6H	10.3	12.2	12.5	12.7	12.9	11.5	13.4	13.7	13.9	14.1
8H	8H	10.3	12.2	12.5	12.7	12.9	11.4	13.4	13.6	13.9	14.1
8H	12H	10.3	12.2	12.5	12.8	12.9	11.4	13.4	13.6	13.9	14.1
12H	4H	10.2	12.2	12.5	12.6	12.9	11.5	13.4	13.7	13.8	14.1
12H	6H	10.2	12.2	12.5	12.7	12.9	11.4	13.4	13.6	13.9	14.1
12H	8H	10.3	12.2	12.4	12.7	12.9	11.4	13.4	13.6	13.9	14.0

Variation av blickförhållning för tvärsnittet S

S = 1.0H	+3.4 / -5.0	+1.0 / -6.0
S = 1.5H	+5.9 / -5.4	+5.6 / -7.1
S = 2.0H	+7.8 / -5.9	+7.6 / -7.7
Standardavb.:	BK01	BK00
Korrektionsfaktor	-5.7	-4.7

Komplettera blickförhållningar relaterade till total ljusförd.