

## Beräkning av bländning enligt UGR

p Tak	80	70	70	50	50	80	70	70	50	50	
p Vägg	60	50	30	50	30	60	50	30	50	30	
p Golv	30	20	20	20	20	30	20	20	20	20	
Rumsstorlek X Y		Blickriktning tvärs till tvärsaxel					Blickriktning längs till tvärsaxel				
2H	2H	25.8	27.4	28.6	28.0	29.2	28.0	29.5	30.7	30.1	31.4
2H	3H	28.1	29.6	30.7	30.3	31.4	30.7	32.3	33.4	32.9	34.0
2H	4H	29.3	30.9	31.9	31.5	32.6	32.1	33.6	34.7	34.3	35.4
2H	6H	30.6	32.1	33.1	32.8	33.8	33.5	35.0	36.0	35.7	36.7
2H	8H	31.3	32.8	33.7	33.5	34.4	34.2	35.7	36.7	36.4	37.4
2H	12H	32.1	33.6	34.5	34.3	35.2	35.0	36.6	37.5	37.3	38.2
4H	2H	27.3	28.8	29.8	29.5	30.5	28.7	30.3	31.3	30.9	32.0
4H	3H	29.7	31.2	32.1	31.9	32.8	31.6	33.2	34.1	33.9	34.8
4H	4H	31.0	32.5	33.4	33.3	34.1	33.2	34.7	35.5	35.4	36.3
4H	6H	32.4	33.9	34.6	34.7	35.4	34.7	36.3	37.0	37.0	37.8
4H	8H	33.1	34.7	35.3	35.4	36.1	35.5	37.1	37.8	37.9	38.5
4H	12H	33.9	35.5	36.1	36.3	36.9	36.5	38.0	38.7	38.8	39.4
8H	4H	31.9	33.4	34.1	34.2	34.9	33.6	35.2	35.8	35.9	36.6
8H	6H	33.5	35.1	35.6	35.8	36.4	35.4	37.0	37.5	37.8	38.3
8H	8H	34.4	36.0	36.5	36.8	37.3	36.4	38.0	38.5	38.8	39.3
8H	12H	35.4	37.0	37.4	37.8	38.2	37.5	39.1	39.5	39.9	40.4
12H	4H	32.1	33.6	34.2	34.4	35.0	33.6	35.2	35.8	36.0	36.6
12H	6H	33.8	35.4	35.9	36.2	36.7	35.5	37.1	37.6	37.9	38.4
12H	8H	34.8	36.4	36.8	37.2	37.7	36.6	38.2	38.6	39.0	39.5

Variation av åskådarposition för tvärsaxeländ S

S = 1.0H	+0.1 / -0.1	+0.1 / -0.1
S = 1.5H	+0.3 / -0.3	+0.2 / -0.2
S = 2.0H	+0.4 / -0.5	+0.4 / -0.4
Standardtabell	BK11	BK12
Korrektionsfaktor	20.7	23.3

Korrigerade bländindikeringar relaterade till totalt ljusflöde