

# Beräkning av blandning enligt UGR

p Tak	60	70	70	50	50	60	70	70	50	50
p Vägg	60	50	30	50	30	60	50	30	50	30
p Golv	30	20	20	20	20	30	20	20	20	20

Rumsstorlek X Y		Blickriktning tvärs till tvärsaxel						Blickriktning längs till tvärsaxel				
2H	2H	23.9	25.8	26.4	26.0	26.6	23.9	25.8	26.4	26.0	26.6	
2H	3H	23.8	25.6	26.2	25.9	26.4	23.8	25.6	26.2	25.9	26.4	
2H	4H	23.7	25.6	26.1	25.9	26.4	23.7	25.6	26.1	25.9	26.4	
2H	6H	23.6	25.5	26.0	25.8	26.3	23.6	25.5	26.0	25.8	26.3	
2H	8H	23.6	25.4	25.9	25.8	26.2	23.6	25.4	25.9	25.8	26.2	
2H	12H	23.5	25.4	25.9	25.8	26.2	23.5	25.4	25.9	25.8	26.2	
4H	2H	23.7	25.6	26.1	25.9	26.4	23.7	25.6	26.1	25.9	26.4	
4H	3H	23.5	25.4	25.9	25.8	26.2	23.5	25.4	25.9	25.8	26.2	
4H	4H	23.4	25.3	25.7	25.7	26.1	23.4	25.3	25.7	25.7	26.1	
4H	6H	23.3	25.3	25.6	25.7	25.9	23.3	25.3	25.6	25.7	25.9	
4H	8H	23.3	25.2	25.5	25.6	25.9	23.3	25.2	25.5	25.6	25.9	
4H	12H	23.2	25.2	25.4	25.6	25.8	23.2	25.2	25.4	25.6	25.8	
8H	4H	23.3	25.2	25.5	25.6	25.9	23.3	25.2	25.5	25.6	25.9	
8H	6H	23.2	25.1	25.3	25.6	25.8	23.2	25.1	25.3	25.6	25.8	
8H	8H	23.1	25.1	25.3	25.6	25.7	23.1	25.1	25.3	25.6	25.7	
8H	12H	23.0	25.0	25.2	25.5	25.6	23.0	25.0	25.2	25.5	25.6	
12H	4H	23.2	25.2	25.4	25.6	25.8	23.2	25.2	25.4	25.6	25.8	
12H	6H	23.1	25.1	25.3	25.6	25.7	23.1	25.1	25.3	25.6	25.7	
12H	8H	23.0	25.0	25.2	25.5	25.6	23.0	25.0	25.2	25.5	25.6	

Variation av åskådarposition för bäravstånd S

S = 1.0H	+5.9 / -21.0	+5.9 / -21.0
S = 1.5H	+8.7 / -21.4	+8.7 / -21.4
S = 2.0H	+10.7 / -22.1	+10.7 / -22.1

Standardtabell	BK00	BK00
Korrektionsfaktor	7.1	7.1

Konjugerade blandindikeringar relaterade till total ljusflöde