

Beräkning av bländning enligt UGR

| p Tak | | 80 | 70 | 70 | 50 | 50 | 80 | 70 | 70 | 50 | 50 |
|-------------|-----|------------------------------------|------|------|------|------|------------------------------------|------|------|------|------|
| p Vägg | | 60 | 50 | 30 | 50 | 30 | 60 | 50 | 30 | 50 | 30 |
| p Golv | | 30 | 20 | 20 | 20 | 20 | 30 | 20 | 20 | 20 | 20 |
| Rumsstorlek | | Blickriktning tvärs till tvärsaxel | | | | | Blickriktning längs till tvärsaxel | | | | |
| X | Y | | | | | | | | | | |
| 2H | 2H | 14.6 | 16.4 | 17.5 | 16.7 | 17.7 | 16.5 | 18.2 | 19.3 | 18.5 | 19.5 |
| 2H | 3H | 14.9 | 16.7 | 17.7 | 17.0 | 17.9 | 17.2 | 18.9 | 19.9 | 19.3 | 20.2 |
| 2H | 4H | 14.9 | 16.7 | 17.6 | 17.0 | 17.9 | 17.5 | 19.2 | 20.2 | 19.6 | 20.5 |
| 2H | 6H | 14.9 | 16.7 | 17.5 | 17.0 | 17.8 | 17.7 | 19.5 | 20.3 | 19.8 | 20.7 |
| 2H | 8H | 14.8 | 16.6 | 17.4 | 17.0 | 17.8 | 17.7 | 19.5 | 20.3 | 19.9 | 20.7 |
| 2H | 12H | 14.8 | 16.6 | 17.4 | 17.0 | 17.7 | 17.7 | 19.5 | 20.3 | 19.9 | 20.7 |
| 4H | 2H | 14.9 | 16.7 | 17.6 | 17.0 | 17.9 | 16.5 | 18.3 | 19.2 | 18.6 | 19.5 |
| 4H | 3H | 15.3 | 17.1 | 17.8 | 17.4 | 18.2 | 17.3 | 19.1 | 19.9 | 19.5 | 20.3 |
| 4H | 4H | 15.3 | 17.1 | 17.8 | 17.5 | 18.2 | 17.7 | 19.5 | 20.2 | 19.9 | 20.6 |
| 4H | 6H | 15.2 | 17.1 | 17.7 | 17.5 | 18.1 | 18.0 | 19.8 | 20.4 | 20.3 | 20.8 |
| 4H | 8H | 15.2 | 17.1 | 17.6 | 17.5 | 18.0 | 18.0 | 19.9 | 20.4 | 20.4 | 20.9 |
| 4H | 12H | 15.2 | 17.0 | 17.5 | 17.5 | 18.0 | 18.0 | 19.9 | 20.4 | 20.4 | 20.8 |
| 8H | 4H | 15.3 | 17.2 | 17.7 | 17.6 | 18.1 | 17.6 | 19.5 | 20.0 | 19.9 | 20.4 |
| 8H | 6H | 15.3 | 17.2 | 17.6 | 17.7 | 18.1 | 17.9 | 19.8 | 20.2 | 20.3 | 20.7 |
| 8H | 8H | 15.2 | 17.1 | 17.5 | 17.6 | 18.0 | 18.0 | 19.9 | 20.3 | 20.4 | 20.7 |
| 8H | 12H | 15.2 | 17.1 | 17.4 | 17.6 | 17.9 | 18.0 | 19.9 | 20.3 | 20.4 | 20.7 |
| 12H | 4H | 15.3 | 17.2 | 17.6 | 17.6 | 18.1 | 17.6 | 19.4 | 19.9 | 19.9 | 20.4 |
| 12H | 6H | 15.2 | 17.2 | 17.5 | 17.7 | 18.0 | 17.9 | 19.8 | 20.1 | 20.3 | 20.6 |
| 12H | 8H | 15.2 | 17.1 | 17.4 | 17.6 | 17.9 | 17.9 | 19.9 | 20.2 | 20.4 | 20.7 |

Variation av åskådarposition för tvärsaxeländ S

| | | |
|-------------------|-------------|-------------|
| S = 1.0H | +0.8 / -1.2 | +0.4 / -0.6 |
| S = 1.5H | +1.2 / -2.3 | +1.3 / -1.1 |
| S = 2.0H | +2.6 / -3.6 | +2.4 / -2.1 |
| Standardtabell | BK01 | BK03 |
| Korrektionsfaktor | -0.9 | 2.4 |

Korrigerade bländindikeringar relaterade till totalt ljusflöde