

Beräkning av bländning enligt UGR

| | | | | | | | | | | | |
|--------------------|-----|------------------------------------|------|------|------|------|------------------------------------|------|------|------|------|
| p Tak | 70 | 70 | 50 | 50 | 30 | 70 | 70 | 50 | 50 | 30 | |
| p Vägg | 50 | 30 | 50 | 30 | 30 | 50 | 30 | 50 | 30 | 30 | |
| p Golv | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | |
| Rumsstorlek X Y | | Blickriktning tvärs till tvärsaxel | | | | | Blickriktning längs till tvärsaxel | | | | |
| 2H | 2H | 20.4 | 21.7 | 20.7 | 22.0 | 22.3 | 18.6 | 19.9 | 18.9 | 20.2 | 20.5 |
| 2H | 3H | 22.4 | 23.6 | 22.7 | 23.9 | 24.2 | 19.8 | 21.0 | 20.2 | 21.3 | 21.7 |
| 2H | 4H | 23.3 | 24.5 | 23.7 | 24.8 | 25.1 | 20.3 | 21.4 | 20.7 | 21.8 | 22.1 |
| 2H | 6H | 24.2 | 25.3 | 24.6 | 25.6 | 26.0 | 20.6 | 21.7 | 21.0 | 22.0 | 22.4 |
| 2H | 8H | 24.6 | 25.6 | 25.0 | 26.0 | 26.4 | 20.7 | 21.7 | 21.1 | 22.1 | 22.5 |
| 2H | 12H | 25.1 | 26.1 | 25.5 | 26.4 | 26.8 | 20.8 | 21.8 | 21.2 | 22.1 | 22.5 |
| 4H | 2H | 21.0 | 22.1 | 21.4 | 22.4 | 22.8 | 19.6 | 20.8 | 20.0 | 21.1 | 21.4 |
| 4H | 3H | 23.2 | 24.2 | 23.6 | 24.6 | 25.0 | 21.1 | 22.1 | 21.5 | 22.4 | 22.8 |
| 4H | 4H | 24.3 | 25.2 | 24.8 | 25.6 | 26.0 | 21.7 | 22.6 | 22.1 | 23.0 | 23.4 |
| 4H | 6H | 25.4 | 26.2 | 25.9 | 26.6 | 27.1 | 22.1 | 22.9 | 22.6 | 23.3 | 23.8 |
| 4H | 8H | 26.0 | 26.7 | 26.4 | 27.1 | 27.6 | 22.3 | 23.0 | 22.8 | 23.4 | 23.9 |
| 4H | 12H | 26.5 | 27.2 | 27.0 | 27.7 | 28.2 | 22.4 | 23.0 | 22.9 | 23.5 | 24.0 |
| 8H | 4H | 24.6 | 25.3 | 25.1 | 25.8 | 26.3 | 22.4 | 23.1 | 22.9 | 23.6 | 24.0 |
| 8H | 6H | 26.0 | 26.6 | 26.5 | 27.0 | 27.6 | 23.1 | 23.7 | 23.6 | 24.1 | 24.7 |
| 8H | 8H | 26.7 | 27.2 | 27.2 | 27.7 | 28.3 | 23.3 | 23.9 | 23.9 | 24.4 | 24.9 |
| 8H | 12H | 27.5 | 27.9 | 28.0 | 28.5 | 29.0 | 23.5 | 24.0 | 24.1 | 24.5 | 25.1 |
| 12H | 4H | 24.6 | 25.3 | 25.1 | 25.8 | 26.3 | 22.6 | 23.2 | 23.1 | 23.7 | 24.2 |
| 12H | 6H | 26.1 | 26.6 | 26.6 | 27.1 | 27.6 | 23.4 | 23.9 | 23.9 | 24.4 | 24.9 |
| 12H | 8H | 26.9 | 27.3 | 27.4 | 27.8 | 28.4 | 23.8 | 24.2 | 24.3 | 24.7 | 25.3 |

Variation av åskådarposition för tvärsaxeländ S

| | | |
|-------------------|-------------|-------------|
| S = 1.0H | +0.1 / -0.1 | +0.1 / -0.1 |
| S = 1.5H | +0.2 / -0.2 | +0.3 / -0.4 |
| S = 2.0H | +0.3 / -0.5 | +0.4 / -0.7 |
| Standardtabell | BK09 | BK06 |
| Korrektionsfaktor | 10.4 | 6.0 |

Korrigerade bländindikeringar relaterade till totalt ljusflöde